

# MenuMap

C511

Printer Serial Number:AK4A026957 Printer Asset Number:  
 CU version:B7.00 [ I01.23 U00.26 S3.52.21 B01.00 266MHz 12711470 000B0001 F50 J0 ]  
 PU version:00.01.17 [ P103.20 L000.00.07 ] ET:0001010403040517331A00550200000F KYMC-0000  
 Hiper-C version:01.01  
 DUPLEX:installed TRAY1:A4  
 Total Memory Size:64 MB P12S12  
 Flash Memory:4 MB [ F50 ]  
 OEL LCD:T2 PNL:T2 MC:CP  
 Network version:01.01 Web Remote:01.00  
 ENGINE:1146 K.276 C.865 T.0.0.0.0, I.0, B.0, F.0

Language format:3.00

INFORMATION MENU  
 PRINT MENU MAP  
 NETWORK  
 DEMO1  
 USAGE REPORT

SNMP  
 NETWORK SCALE  
 HUB LINK SETTING  
 TCP ACK  
 FACTORY DEFAULTS

ENABLE  
 NORMAL  
 AUTO NEGOTIATE  
 TYPE1

## PRINT MENU

COPIES 1  
 DUPLEX LAST PAGE SKIP BLANK PAGE  
 PAPER FEED TRAY1  
 AUTO TRAY SWITCH ON  
 TRAY SEQUENCE DOWN  
 MP TRAY USAGE DO NOT USE  
 MEDIA CHECK ENABLE  
 OVERRIDE A4/LT YES  
 MONO-PRINT SPEED AUTO

## MAINTENANCE MENU

MENU RESET  
 SAVE MENU  
 POWER SAVE  
 SLEEP  
 AUTO PW OFF  
 PAPER BLACK SET  
 PAPER COLOR SET  
 SMR SETTING  
 BG SETTING

ENABLE  
 ENABLE  
 AUTO CONFIG  
 0  
 0  
 0  
 0

## MEDIA MENU

TRAY1 PAPERSIZE A4  
 TRAY1 MEDIATYPE PLAIN  
 TRAY1 MEDIAWEIGHT MEDIUM  
 MPT PAPERSIZE A4  
 MPT MEDIATYPE PLAIN  
 MPT MEDIAWEIGHT MEDIUM  
 UNIT OF MEASURE MILLIMETER

## USAGE MENU

TRAY1 COUNT 1146  
 MP TRAY COUNT 0  
 DRUM UNIT LIFE  
 BELT LIFE  
 FUSER LIFE  
 K TONER (2.0K)  
 C TONER (2.0K)  
 M TONER (2.0K)  
 Y TONER (2.0K)

REMAINING 99 %  
 REMAINING 84 %  
 REMAINING 91 %  
 REMAINING 100 %  
 REMAINING 10 %  
 REMAINING 100 %  
 REMAINING 10 %

## COLOR MENU

DENSITY CONTROL  
 ADJUST DENSITY  
 AJST REGISTRATION  
 C REG FINE AJST  
 M REG FINE AJST  
 Y REG FINE AJST

AUTO  
 0  
 0  
 0

## SYS CONFIG MENU

POW SAVE TIME 1 MIN  
 SLEEP TIME 30 MIN  
 AUTO PW OFF TIME 4 HOURS  
 CLRABLE WARNING ONLINE  
 MANUAL TIMEOUT 60 SEC  
 WAIT TIMEOUT 90 SEC  
 LOW TONER CONTINUE  
 JAM RECOVERY ON  
 ERROR REPORT OFF

## USB MENU

SOFT RESET  
 SPEED 480Mbps  
 SERIAL NUMBER ENABLE

## NETWORK MENU

TCP/IP  
 IP ADDRESS SET  
 IPV4 ADDRESS 192.168.71.89  
 SUBNET MASK 255.255.255.0  
 GATEWAY ADDRESS 192.168.71.100  
 WEB  
 TELNET  
 FTP

ENABLE  
 MANUAL  
 192.168.71.89  
 255.255.255.0  
 192.168.71.100  
 ENABLE  
 DISABLE  
 DISABLE